

VuOxi Floating Aerator 3,0 kW (4.0 hp)

VuOxi Floating Aerators are CE marked products from Finland.

Technical data

Oxygen transfer efficiency	Up to 2,0 kgO ₂ /kWh* (3.2 lbO ₂ /hp-hr)
Spray pattern diameter	Appr. 4,50 m (14.8 ft)
Motor	3-phase customized motor manufactured by Lönne or equal (CE, UL and CSA approved)
Nominal power	3,0 kW (4.0 hp)
Efficiency class	IE3
Insulation class	H
V/F	50 Hz: 400 V +- 5%, 5,9 A; 60 Hz: 460 V +- 5%, 5,9 A
Electrical cable	4G2,5 European standard cable. Note: Length and local electrical control system may affect. When using AC-drive EMC-cable or shielded cable is required
Main dimensions	1200 mm x 1200 mm x 800 mm (47.2" x 47.2" x 31.5")
Weight of aerator with floats	Appr. 110 kg (265 lb)
Materials	× Metals AISI 304 × Impeller plastic × Float PE-plastic × Intake pipe** PE-plastic

Optional features


- Frequency converter (AC-drive)
 - × Protection class IP21 or IP55
 - × Automatic impeller cleaning cycle feature

Metal parts AISI 316

Intake pipe screen

Lifting hook

Shallow pond protect



* Oxygen measurement accuracy $\pm 15\%$

** Customer must define the length of the intake pipe (the pipe should be 1,0 – 2,5 m / 3.3 - 8.2 ft above the bottom of the basin, depends on basins material).

Information without engagement. All rights to changes without prior notice reserved.